

Hybrid PTZ Dome camera

IP Surveillance Camera




Key Features

- 1 / 2.8" progressive , 16 optical zoom
- Auto iris, auto focus, auto white balance, BLC and 3D DNR
- HD network video output : 2048 × 1536 @30fps
- HD analog video output : AHD and TVI optional, 1920 × 1080 @30fps
- H.265 and H.264 image compression format
- TCP / IP, UDP, DHCP, DDNS, NTP, RTSP, SMTP, FTP, PPPoE, IPv4 / IPv6
- SD card local storage, network remote storage
- Efficient IR array to assist in illumination, low power consumption and up to 120m IR night view distance
- IR LEDs and matching algorithm for ideal image condition by adjusting the brightness and angle of the IR LEDs based on the zoom ratio and distance
- Built-in heat treatment device to lower the inside temperature and avoid fogging of the camera rear cover
- Using 3D intelligent position function through the DVR, client software and IE to realize tracking and amplification
- Power off memory — restoring the PTZ and lens status automatically to its previous status
- IP66 ingress protection; TVS 6KV lightning protection, surge protection
- 1 CH audio input and 1 CH audio output
- Precision motor driving, sensitive and responsive, smoothly running,
- Less than 0.1° precision error and no image floating at any speed
- Support home position function

Specification

CAMERA	
Image Sensor	1 / 2.8 " Progressive Scan CMOS Sensor
Image Size	3MP (2048 x 1536)
White Balance	Auto / Manual
AGC	Auto / Manual
Min. illumination	0.05 lux @F1.2,AGC ON; 0 lux with IR
3D DNR	Yes
Day & Night	ICR
LENS	
Lens	5.5 ~ 110 mm - 20X optical zoom
FUNCTION	
Pan Range	360° endless rotation
Pan Speed	Manual control speed: 0.1° ~ 120°/s; preset speed: 240°/s
Tilt Range	0 ~ 90°
Tilt Speed	Manual control speed: 0.1° ~ 90°/s; preset speed: 200°/s
Zoom	Yes
Preset	360 presets
Cruise	8 cruises, 16 presets for each cruise
Scan	2 scans
Track	4 tracks, 3 minutes' recording for each track
Time Task	Yes
Home Position	Yes
Power Off Memory	Yes
IR Function	
IR Distance	120 m
IR Control	Brightness and angle of the IR LEDs to be smartly adjusted according to the scenes
Network	
Max Image Size	2048 × 1536
Resolution	3MP (2048 × 1536), 2MP (1920 × 1080), 1.3MP (1280 × 960), VGA (640 × 480)
Video Compression	H.265 / H.264 / MJPE
Audio Compression Protocol	G.711A / G.711U
Network Protocol	TCP / IP, UDP, DHCP, DDNS, NTP, RTSP, SMTP, FTP, PPPoE, IPv4 / IPv6
Online user	max. 10
HD Analog	
Max. Image Size	1920 × 1080
Video Output	AHD and TVI optional
System Integration	
Alarm Input	4 CH (5 ~ 12V DC
Alarm Output	1 CH, support alarm trigger (preset, snap, FTP upload and email trigger)
Network Interface	Built-in RJ45 network port, support 10M / 100M network data
SD Card Interface	Built-in Micro SD card slot, support manual recording
API	API, SDK, ONVIF, GB / T28181
Analog HD Output	BNC
Web Client	Web 4.0
General Specifications	
OSD Menu	Chinese / English
Power Supply	DC24V 3000 mA (15W, max 65W)
Working Environment	-30 ~ 60°C; humidity: less than 90%
Water-proof	Ip66
Protection Level	Ik10, TVS6KV lightning protection, surge protection

Design and specifications are subject to change without notice.



Sensor



Min. Illumination



WDR



Motion Detection



Day&Night



AWB



Sync



AGC



IR range



Water-proof