VT-A52DV30-2S

2 MP IR Water-proof Dome Camera



DOME

AHD/TVI/CVI/CVBS Camera



Key Features

- 1080P real time image, high resolution, true color
- AHD lossless video output
- CMOS progressive scan, perfectly capture the moving object
- Support OSD menu
- High speed, long distance, real time transmission
- Auto color to B / W at low illumination
- Support ICR switch, true day / night
- Support noise reduction function
- 30m IR night view distance
- IP66 ingress protection
- Support COC
- Support 960H CVBS output











Sensor

Min. Illumination

WDR

Resolution Day&Night











AWB

Sync

AGC

IR Distance Water-proof

Specification CAMERA Image Sensor 1 / 2.9 " Progressive Scan CMOS Sensor Resolution 1920 x 1080 PAL / NTSC **Image System** Auto Iris Fixed Iris 0.01 lux @F1.2,AGC ON; 0 lux with IR Min. illumination $2.8 \sim 12$ mm, angle of view: $98.2^{\circ} \sim 30^{\circ}$ Lens Lens Mount IR Distance ~30 m Water-proof IP 66 Video Output AHD/TVI/CVI/CVBS selectable from COC menu Image Size 1080P (1920 x 1080) Frame Rate 30fps (60Hz), 25fps (50Hz) Angle Adjustment Any angle Functions 2 languages supported, Chinese / English Screen Display OSD (COC Control) **Function Control** Day & Night Yes (ICR) BLC & HLC Yes Digital WDR **WDR** Digital NR Yes **Defect Correction** Live defective pixel correction

Others	
Power Supply	DC12V (±10%)
Power Consumption	< 2W
IR Consumption ON	<6W
Working Environment	-30°C ~ 50 °C, 10% ~ 90% humidity
Dimensions (mm)	Ф109 х 130
Weight (net)	689 g.

> 52dB (AGC off)

are adjustable

1/50s ~ 1/100000s (PAL);

1/60s ~ 1/100000s (NTSC);

ATW, AWC->SET, Manual

Sharpness, saturation, brightness, etc.

Design and specifications are subject to change without notice

Dimensions

S / N Ratio

AGC

Electronic Shutter

White Balance

Advanced Image







