

Starlight BULLET AHD/TVI/CVI/CVBS 4 in 1 Camera



Key Features

- 1080P real time image, high resolution, true color
- AHD / TVI / CVI / CVBS video output
- Starlight, WDR 120dB, 3D DNR
- CMOS progressive scan, perfectly capture the moving object Support OSD menu
- High speed, long distance, real time transmission
- Auto color to B / W at low illumination
- Support ICR switch, true day / night
- Support noise reduction function
- 50m IR night view distance
- IP66 ingress protection
- Support COC
- Support 960H CVBS output

VT-H53EZV50S-2AM

2 MP Hibrid 4 in 1 STARLIGHT (Water-proof) Bullet Camera MOTORIZED ZOOM



| Specification | |
|---------------------|-------------------------------------------------------------|
| CAMERA | |
| Image Sensor | 1 / 2.8 " Progressive Scan CMOS Sensor |
| Resolution | 1920 x 1080 |
| Image System | PAL / NTSC |
| Auto Iris | Fixed Iris |
| Min. illumination | Color : 0.001 lux@F1.2, AGC ON; B/W : 0 lux with IR |
| Lens | Motorized 2.8 ~12 mm, angle of view: 105° ~ 32°, AUTOFOCUS |
| Lens Mount | D14 |
| IR Distance | ~50 m |
| Water-proof | IP 66 |
| Video Output | AHD /TVI/CVI/CVBS output switch available from camera cable |
| Image Size | 1080P (1920 x 1080) |
| Frame Rate | 30fps (60Hz), 25fps (50Hz) |
| Angle Adjustment | Any angle |
| Functions | |
| Screen Display | 13 different languages |
| Function Control | OSD - COC Control |
| Day & Night | Yes (ICR) |
| BLC & HLC | Yes |
| WDR | 120dB |
| Digital NR | Yes |
| Defect Correction | Live defective pixel correction |
| S / N Ratio | > 52dB (AGC off) |
| Electronic Shutter | 1/50s ~ 1/100000s (PAL); 1/60s ~ 1/100000s (NTSC); |
| AGC | Yes |
| White Balance | ATW, AWC->SET, Manual |
| Advanced Image | Sharpness, saturation, brightness, etc. are adjustable |
| Others | |
| Power Supply | DC12V (±10%) |
| Power Consumption | < 2W |
| IR Consumption ON | < 7W |
| Working Environment | -30°C ~ 50 °C, 10% ~ 90% humidity |
| Dimensions (mm) | Ф109 × 284 |
| Weight (net) | 1100g. |

Design and specifications are subject to change without notice.



Sensor

-8-



Sync







AWB

AGC

IR Distance Water-proof







Dimensions

