

Network Video Recorder
H.265 compression



HD Output



HD IPC



Network



CMS



STD

Key Features

- Support 4/8/16 CH IP camera 5MP / 4MP / 3MP / 1080P / 720P IP input
- Adopt standard H.265 high profile compression format to get high-quality video at much lower bit rate
- 1080P HDMI output, true high resolution display
- Intuitive and user-friendly Graphic User Interface (GUI), Windows style operation by mouse
- Multi-mode recording: manual / timer / motion / sensor
- Playback : 4 / 8 / 16 CH simultaneous playback
- Search : time slice, time, event (manual, sensor, motion), tag search
- Express and flexible backup via USB, network and so on
- Pentaplex : preview, record, playback, backup and remote access
- DHCP, DDNS, PPPoE network protocol and CMS supported
- Remote control via IE or CMS : preview, playback, backup, PTZ and configuration
- Dual stream technology for local storage with high definition, remote network transmission and remote surveillance with mobile device
- Multi-user online simultaneously
- Authorization management, log view and device status view
- Support PTZ preset and auto cruise, up to 255 presets and 8 cruises
- Support NAT function and QRCode scanning by mobile phone and PAD
- Powerful smart phone & Pad surveillance with iOS and Android OS

Specification		VT-N1304B	VT-N1308B	VT-N1316B
System	Compression	Standard H.265 High Profile		
	OS	Embedded Linux		
Video	Network Input	4 Ch. IPC input	8 Ch. IPC input	16 Ch. IPC input
	Access Bandwidth	40Mbps	64Mbps	80Mbps
	Network Access Format	5MP / 4MP / 3MP / 1080P / 960P / 720P@25 / 30fps		
Audio	Output	HDMI × 1 : 1920×1080/1280×1024/1024×768 VGA × 1 : 1920×1080/1280×1024/1024×768		
	Network Input	4 Ch. IPC audio	8 Ch. IPC audio	16 Ch. IPC audio
Record	Record Stream	Dual stream recording		
	Resolution	5MP / 4MP / 3MP / 1080P / 960P / 720P		
	Mode	Manual, timer, motion		
Playback	Simultaneous Playback	max. 4 CH	max. 8 CH	max. 16 CH
	Search	Time slice / time / event / tag search		
	Smart Search	Highlighted color to display the camera record in a certain period of time, different colors refers to different record events		
Alarm	Function	Play, pause, FF, FB, digital zoom, etc.		
	Mode	Manual, motion, exception		
	Input	4 Ch. IPC alarm IN	8 Ch. IPC alarm IN	16 Ch. IPC alarm IN
Network	Output	No		
	Triggering	Record, snap, preset, e-mail, etc.		
Mobile Device	Interface	RJ45 10/100Mbps × 1		
	Protocol	TCP/IP, PPPoE, DHCP, DNS, DDNS, UPnP, NTP, SMTP		
	Web Client	Multiple users online		
Storage	OS	iOS, Android		
	Local Backup	U disk, USB removable HDD		
Port	HDD	SATA × 1, max. 6 T		
	Network Backup	Yes		
Others	USB	USB 2.0 × 2 (one in the front panel and the other in the rear panel)		
	Remote Cont.	Optional (Remote Controller)		
Power Supply	Power Supply	DC 12V		
	Consumption	≤ 6W (without HDD)		≤ 10W (without HDD)
	Dimensions	255 × 233 × 42 (W × D × H) mm		
	Work Temp.	Work Environment -10 ~ 50°C, 10% ~ 90% humidity		

Design and specifications are subject to change without notice.

Dimensions

