## VT-N1304/08B-4/8P

5MP / 4MP / 3MP / 1080P / 960P / 720P HD PoE NVR



## **Network Video Recorder with PoE** H.265 compresion





PoE ports



HD IPC



Network





CMS

STD

## **Key Features**

- Support 4 / 8 CH 5MP / 4MP / 3MP / 1080P / 960P / 720P IP input
- Adopt standard H.265 high profile compression format to get high-quality video at much lower bit rate
- Intuitive and user-friendly Graphic User Interface (GUI),
  Windows style operation by mouse
- $\blacksquare \ \, \mathsf{Multi-mode} \ \mathsf{recording:} \ \mathsf{manual} \, \mathsf{/} \, \mathsf{timer} \, \mathsf{/} \, \mathsf{motion} \, \mathsf{/} \, \mathsf{sensor}$
- Playback: 4 / 8 CH simultaneous playback
- Search: time slice, time, event (manual, sensor, motion), tag search
- Express and flexible backup via USB, network and so on
- Pentaplex: preview, record, playback, backup and remote access
- DHCP, DDNS, PPPoE network protocol and CMS supported
- Remote control via IE or CMS : preview, playback, backup, PTZ and configuration
- 4 / 8 PoE network ports, support IPC direct connection to NVR; support PoE power supply
- Dual stream technology for local storage with high definition, remote network transmission and remote surveillance with mobile device
- Multi-user online simultaneously
- Authorization management, log view and device status view
- $\blacksquare$  1080P output, true high resolution display
- Support PTZ preset and auto cruise, up to 255 presets and 8 cruises
- Support NAT function and QRCode scanning by mobile phone and PAD
- Powerful smart phone & Pad surveillance with iOS and Andriod OS

Specification		VT-N1304B-4P	VT-N1308B-8P	
System	Compression	Standard H.265 High Profile		
	OS	Embedded Linux		
Video	Network Input	4 Ch. IPC input	8 Ch. IPC input	
	Acces Bandwidth	32Mbps	64Mbps	
	Network Access Format	5MP / 4MP / 3MP / 1080P / 960P / 720P@25 / 30fps		
	Output	HDMI × 1:1920×1080/1280×1024/1024×768 VGA × 1:1920×1080/1280×1024/1024×768		
Audio	Network Input	4 Ch. IPC audio	8 Ch. IPC audio	
	2-way Audio	NO		
	Local Output	No ( HDMI supports the audio output )		
Record	Record Stream	Dual stream recording		
	Resolution	5MP / 4MP / 3MP / 1080P / 960P / 720P		
	Mode	Manual, timer, motion		
	Simultaneous Playback	max. 4 CH	max. 8 CH	
Dlaubaek	Search	Time slice / time / event / tag search		
Playback	Smart Search	Highlighted color to display the camera record in a certain period of time, different colors refers to different record events		
	Function	Play, pause, FF, FB, digital zoom, etc.		
Alarm	Mode	Manual, motion, exception		
	Input	4 CH IPC alarm input	8 CH IPC alarm input	
	Output	No		
	Triggering	Record, snap, preset, e-mail, etc.		
Network	Interface	RJ45 10/100Mbps × 1		
	PoE Port	10/100 Mbps - Rj45 × 4	10/100 Mbps - Rj45 × 8	
	Protocol	TCP/IP, PPPoE, DHCP, DNS, DDNS, UPnP, NTP, SMTP		
	Web Client	Multiple users online		
Mobile Device	OS	iOS, Andriod		
Storage	HDD	SATA × 1, max. 8 T		
Backup	Local Backup	U disk, USB removable HDD		
	Network Backup	Yes		
Port	USB	USB 2.0 $\times$ 2 ( one in the front panel and the other in the rear panel)		
	Remote Cont.	Optional (Remote Controller )		
Others	Power Supply	DC48V/1.25A	DC48V/2.5A	
	Consumption	≤ 6W (without HDD and PoE)		
	Dimensions	255 × 233 × 42 mm (W × D × H)		
	Work Temp.	Work Environment -10 ~ 50°C, 10	0% ~ 90% humidity	

Design and specifications are subject to change without notice.

## Dimensions





