

10 W 8" round wall or ceiling surface mount loudspeaker, metal



Part-No.: 582424

Approval: Part of EN 54-16 approval

The loudspeaker DL-A 10-200/T-EN 54 for voice alarm made of powder-coated metal in white with high degree of efficiency and a high-quality 200 mm broadband loudspeaker chassis.

The DL-A 10-200/T EN 54 can be mounted onto ceilings and walls when recessed mounting is not possible. Flat and elegant design for unobtrusive installations provided with a metal back plate. The loudspeaker features a ceramic terminal and a thermal fuse in order to meet the highest safety requirements. The chassis is impregnated against moisture. Apart from a very high safety standard, the DL-A 10-200/T EN 54-24 also features a powerful sound.

Features:

- Completely detachable
- Pivoting frame and door with little effort in hinge is changeable

Rated Power	10 W
Sensitivity EN 54-24, 1 W / 1 m	92,5 dB
Sensitivity EN 54-24, max 1 m	102 dB
Transmission range	275 Hz ... 19100 Hz
Ambient temperature	-20 °C ... 80 °C
Color	white, similar to RAL 9010
Weight	approx. 2,1 kg
Dimensions	Ø: 210 mm D: 90 mm



Pivot frame Welded 100 mm plinth, with holes for floor mounting and cable entry Rear and side walls detachable, on request, and ventilated Three-part base plate Roof with a brush strip and cover plate Front door with a 4 mm ESG pane Door lock with a swivel lever for 40 mm PHZ and multi point locking Cabinet completely grounded Screws set M6 (VE 50 set)



Delivery time on request

Accessories:

584921	Angled Sliding Rail (set) 250 mm deep, for hinged frames
584922	Cable Clamping Rail Set, 2 HU