

## Linea LEN-150 EN 54-24, black



### Part-No.: 582657.B

Passive 100 V loudspeaker, with weatherproof aluminium housing, designed for use with voice alarm systems - certified according to EN 54-24, Type B, equipped with two high-quality 4" drivers with treated cones for optimum efficiency in speech and voice alarms.

|                                      |  |
|--------------------------------------|--|
| SPL Pmax / 1 m                       | 118 dB   |
| Sensitivity EN 54-24, 1 W / 4 m_comp | 86 dB  |
| Dispersion angle                     | 130° (H) x 14° (V) nominal; 360° (H) x 35° (V) @500 Hz; 190° (H) x 20° (V) @ 1000 Hz; 120° (H) x 14° (V) @ 2000 Hz; 95° (H) x 8° (V) @ 4000 Hz |
| Housing                              | weatherproof aluminium housing, powder coated, steel bracings  |
| Color                                | black, similar to RAL 9005, powder-coated  |
| Weight                               | approx. 14,5 kg  |
| Dimensions                           | W: 130 mm H: 1460 mm D: 120 mm   |

### Features:

- EN 54-24 certified, 100 V loudspeaker for use with voice alarm systems
- suitable for both indoor and outdoor use
- exceptionally even sound dispersion
- SIDE LOBE FREE – passive realization
- equipped with high performance speakers
- excellent speech intelligibility and sound quality
- a long reach
- weatherproof without requiring additional protection (protection class IP54 in accordance with IEC 529 / EN 60529)
- ball impact resistant front grille made from galvanised sheet steel

### Accessories:

582614.B                      Wall mount WLX-100, black