

581272 (L-PHP30A) 30 W Horn Loudspeaker

- ✓ High impact fire resistant ABS material
- ✓ Lower maintenance cost
- ✓ Rust and chemical resistant
- ✓ Water and dust protected to IP 66
- ✓ CE and RoHS compliant



Overview

L-PHP30A is a 30 W full-range horn loudspeaker designed for high power handling and reliability. Taps on the primary winding allow different power settings. Housing is made of sturdy ABS fire resistant material with high strength and low weight.


With its aesthetical and stylish design, it can be installed in various applications such as train stations, harbors, plazas, police stations, government administrations, tourist destinations, educational institutes, transport hubs and office buildings. The horn is attached with strong and adjustable mounting brackets which help to accurately direct the sound beam. The loudspeaker is CE and RoHS compliant.

Mounting


The horn loudspeaker is supplied with sturdy adjustable mounting brackets, allowing the sound beam to be accurately directed.

Power setting


The horn loudspeaker includes a 100 V transformer with taps on the primary winding to allow different power settings. Nominal full-power, half-power can easily be selected by connecting the amplifier output to the appropriate tap.




Frequency Response









Polar Diagram

Specifications

-	
Electrical	
Max. power	45 W
Rated power	30 W
Power tapping	30 W / 15 W
SPL @ 30 W / 1 m (330 ~ 8 kHz)	116 dB
SPL @ 1 W / 1 m (330 ~ 8 kHz)	104 dB
Frequency range (- 10 dB)	300 Hz ~ 10 kHz
Dispersion angle (1 kHz / - 6 dB)	150 °
Rated input voltage	100 V / 70 V
Rated impedance	$667~\Omega$ / $333~\Omega$
Connection	Flexible wire
Mechanical	
Dimensions	285 mm x 205 mm x 290 mm
Weight	2.10 kg
Color	White (RAL 9003)
Material	ABS
IP rating	IP 66
Environmental	
Operating temperature	- 25 °C + 55 °C
Storage temperature	- 40 °C + 70 °C
Relative humidity	< 95 %

Order information	Part No.
Catalog description	30 W horn loudspeaker
Part number	581272
Туре	L-PHP30A

Honeywell Life Safety Austria GmbH Lemböckgasse 49, 1230 Vienna, Austria Phone: +43 1 600 6030 Fax: +43 1 600 6030-900 www.hls-austria.com

France
Novar France
Isle d'Abeau - Parc de Chesnes
8, place de l'Europe - BP 7401
38074 Saint Quentin Fallavier Cedex
Phone: +33 810 10 66 10 Fax: +33 474 94 51 18 www.esser-systems.com/fr

Germany Novar GmbH Dieselstraße 2, 41469 Neuss, Germany Phone: +49 2131 40615-600 Fax: +49 2131 40615-606 www.esser-systems.com

United Kingdom Notifier By Honeywell Caburn House 2B Brooks Road Lewes, BN7 2BY Phone: +44 116 246 2255 Fax: +44 1444 230 88 www.notifier fire systems.co.uk

Netherlands Honeywell Life Safety Novar Nederland B.V. Oeverkruid 14 4941 VV Raamsdonksveer Phone: +31 162 520290 Fax: +31 162 517858 www.novar.nl

Honeywell Life & Safety AS Terminalen14, Lierstranda Industriområde, 7414 Lierstranda Postboks 3514, 3007 Drammen Phone: +47 32 24 48 00 Fax: +47 32 24 48 01 hls-eltek.no