

U/UTP 4Pairs cable-category5E-PVC Sheath

Content of the Data Sheet

Sheath Printing	HIKVISION E484059-Z CM (UL) 4PR 24AWG 75°C U/UTP CAT5E VERIFIED TO ANSI/TIA-568-C.2 PVC ****m mm/dd/yyyy																																																																																																						
Customer Reference	DS-1LN5E-S																																																																																																						
Category	U/UTP CAT5E-4P- PVC-CM																																																																																																						
Reference Standard	ISO/IEC11801、TIA-568-C.2、UL444																																																																																																						
Conductor	Material	Solid-Bare Copper																																																																																																					
	Nom.O.D.(mm)	0.500 (24AWG)	Content 99.95%																																																																																																				
Insulation	Material	HDPE																																																																																																					
	Diameter	0.88±0.04mm																																																																																																					
Sheath	Thickness	0.50±0.05 mm		Technical Performance (100m) : <table border="1"> <thead> <tr> <th>Frequency (MHz)</th> <th>RL ≥dB</th> <th>ATT (20°C) ≤dB</th> <th>NEXT ≥dB</th> <th>Phase DELAY ≤ns</th> </tr> </thead> <tbody> <tr><td>1</td><td>20.0</td><td>2.0</td><td>65.3</td><td>570.00</td></tr> <tr><td>4.0</td><td>23.0</td><td>4.1</td><td>56.3</td><td>552.00</td></tr> <tr><td>8.0</td><td>24.5</td><td>5.8</td><td>51.8</td><td>546.73</td></tr> <tr><td>10.0</td><td>25.0</td><td>6.5</td><td>50.3</td><td>545.38</td></tr> <tr><td>16.0</td><td>25.0</td><td>8.2</td><td>47.2</td><td>543.00</td></tr> <tr><td>20.0</td><td>25.0</td><td>9.3</td><td>45.8</td><td>542.05</td></tr> <tr><td>25.0</td><td>24.3</td><td>10.4</td><td>44.3</td><td>541.20</td></tr> <tr><td>31.25</td><td>23.6</td><td>11.7</td><td>42.9</td><td>540.44</td></tr> <tr><td>62.5</td><td>21.5</td><td>17.0</td><td>38.4</td><td>538.55</td></tr> <tr><td>100</td><td>20.1</td><td>22.0</td><td>35.3</td><td>537.60</td></tr> </tbody> </table> <table border="1"> <thead> <tr> <th>Frequency (MHz)</th> <th>PSNEXT ≥dB</th> <th>ELFEXT ≥dB</th> <th>PSELFEXT ≥dB</th> </tr> </thead> <tbody> <tr><td>1</td><td>62.3</td><td>63.8</td><td>60.8</td></tr> <tr><td>4</td><td>53.3</td><td>51.8</td><td>48.8</td></tr> <tr><td>8</td><td>48.8</td><td>45.7</td><td>42.7</td></tr> <tr><td>10</td><td>47.3</td><td>43.8</td><td>40.8</td></tr> <tr><td>16</td><td>44.4</td><td>39.7</td><td>36.7</td></tr> <tr><td>20</td><td>42.8</td><td>37.8</td><td>34.8</td></tr> <tr><td>25</td><td>41.3</td><td>35.8</td><td>32.8</td></tr> <tr><td>31.25</td><td>39.9</td><td>33.9</td><td>30.9</td></tr> <tr><td>62.5</td><td>35.4</td><td>27.9</td><td>24.9</td></tr> <tr><td>100</td><td>32.3</td><td>23.8</td><td>20.8</td></tr> </tbody> </table>	Frequency (MHz)	RL ≥dB	ATT (20°C) ≤dB	NEXT ≥dB	Phase DELAY ≤ns	1	20.0	2.0	65.3	570.00	4.0	23.0	4.1	56.3	552.00	8.0	24.5	5.8	51.8	546.73	10.0	25.0	6.5	50.3	545.38	16.0	25.0	8.2	47.2	543.00	20.0	25.0	9.3	45.8	542.05	25.0	24.3	10.4	44.3	541.20	31.25	23.6	11.7	42.9	540.44	62.5	21.5	17.0	38.4	538.55	100	20.1	22.0	35.3	537.60	Frequency (MHz)	PSNEXT ≥dB	ELFEXT ≥dB	PSELFEXT ≥dB	1	62.3	63.8	60.8	4	53.3	51.8	48.8	8	48.8	45.7	42.7	10	47.3	43.8	40.8	16	44.4	39.7	36.7	20	42.8	37.8	34.8	25	41.3	35.8	32.8	31.25	39.9	33.9	30.9	62.5	35.4	27.9	24.9	100	32.3	23.8	20.8
	Frequency (MHz)	RL ≥dB	ATT (20°C) ≤dB		NEXT ≥dB	Phase DELAY ≤ns																																																																																																	
	1	20.0	2.0		65.3	570.00																																																																																																	
	4.0	23.0	4.1		56.3	552.00																																																																																																	
	8.0	24.5	5.8		51.8	546.73																																																																																																	
10.0	25.0	6.5	50.3		545.38																																																																																																		
16.0	25.0	8.2	47.2		543.00																																																																																																		
20.0	25.0	9.3	45.8		542.05																																																																																																		
25.0	24.3	10.4	44.3		541.20																																																																																																		
31.25	23.6	11.7	42.9		540.44																																																																																																		
62.5	21.5	17.0	38.4	538.55																																																																																																			
100	20.1	22.0	35.3	537.60																																																																																																			
Frequency (MHz)	PSNEXT ≥dB	ELFEXT ≥dB	PSELFEXT ≥dB																																																																																																				
1	62.3	63.8	60.8																																																																																																				
4	53.3	51.8	48.8																																																																																																				
8	48.8	45.7	42.7																																																																																																				
10	47.3	43.8	40.8																																																																																																				
16	44.4	39.7	36.7																																																																																																				
20	42.8	37.8	34.8																																																																																																				
25	41.3	35.8	32.8																																																																																																				
31.25	39.9	33.9	30.9																																																																																																				
62.5	35.4	27.9	24.9																																																																																																				
100	32.3	23.8	20.8																																																																																																				
Surface Printing	Letter height	3.0±0.3mm																																																																																																					
	Color	Black																																																																																																					
	Print error & Space	≤±0.5%, 1m																																																																																																					
Core Color	1 White- Blue /Blue	2 White-Orange /Orange																																																																																																					
	3 White- Green /Green	4 White- Brown /Brown																																																																																																					
Packing	Wooden Tray & Carton																																																																																																						
Carton dimension	Per request																																																																																																						
Packing length	(305±1.5)m																																																																																																						
Rip-cord	Yes	Drain wire	No																																																																																																				
Sheath Physical Properties	Before Aging Tensile Strength (Mpa)	≥13.5																																																																																																					
	Elongation(%)	≥150																																																																																																					
	Aging Period(°C×hrs)	100°C×24h×10d																																																																																																					
	After Aging Tensile Strength(Mpa)	≥12.5																																																																																																					
	Elongation(%)	≥125																																																																																																					
Electrical Characteristics (20°C)	1.0-100.0MHz Impedance(Ω)	100±15																																																																																																					
	1.0-100.0MHz Delay Skew (ns/100m)	≤45																																																																																																					
	DC Resistance(Ω/100m) max	9.5																																																																																																					
	DC Conductor Resistance Unbalance(%) max	5.0																																																																																																					
Ambient temperature:	-20°C - 75°C		Operating Voltage: 80V																																																																																																				