



SFP Dual Wavelength Single-Mode LC Module TEG-MGBS10D3 (v4.0R)

The hot-pluggable TEG-MGBS10D3 must be paired with the TEG-MGBS10D5 or other compatible module. This SFP Dual Wavelength Single Mode LC Type module spans distances of up to 10 kilometers (6.2 miles). The SFP interface is compatible with standard SFP slots and offers a 1000 Mbps-LX SFP interface.

PRODUCT OVERVIEW

- Must pair with TEG-MGBS10D5 or other compatible module
- LC Simplex connector-type
- Dual wavelength fiber mode
- Spans distances up to 10 km (6.2 miles)
- Compatible with standard SFP slots

FEATURES

- Must pair with TEG-MGBS10D5 or other compatible module
- Compliant with IEEE 802.3z
- ANSI Fiber Channel compliant
- Compliant with Small Form-Factor Pluggable (SFP) Multi-Source Agreement (MSA) ports
- Supports data rate of up to 1.25 Gbps
- Transmission distance of up to 10 km (6.2 miles)
- Metal Enclosure with low Electromagnetic Interference (EMI) design
- Simplex LC optical interface
- Hot pluggable
- Low power consumption
- Lifetime Warranty*

SFP Dual Wavelength Single-Mode LC Module

TEG-MGBS10D3 [v4.0R]



SPECIFICATIONS

HARDWARE

Standards	<ul style="list-style-type: none"> • IEEE 802.3z • ANSI Fiber Channel compliant • Class 1 Laser
Interface	<ul style="list-style-type: none"> • SFP MSA Compliant • Simplex LC optical interface
Power Consumption	<ul style="list-style-type: none"> • Max. 0.8 Watts
Dimension	<ul style="list-style-type: none"> • 57 x 13 x 12 mm (2.2 x 0.5 x 0.5 in.)
Weight	<ul style="list-style-type: none"> • 18 g (0.6 oz.)
Temperature	<ul style="list-style-type: none"> • Operating: 0°C ~ 70°C (32°F ~ 158°F) • Storage: -40°C ~ 85°C (-40°F ~ 185°F)
Humidity	<ul style="list-style-type: none"> • Max 85% (non-condensing)
Certifications	<ul style="list-style-type: none"> • CE, FCC

Model	Wavelength	Optical Output Power (dBm)		Optical Input Power (dBm)		Power Budget	Distance	
		Min	Max	Min (Sensitivity)	Max			
TEG-MGBSX	850 nm	-9	-3	-20	-3	-11	550 m	
TEG-MGBS10	1310 nm	-9	-3	-22	-3	-13	10 km	
TEG-MGBS40	1310 nm	-3	2	-23	-3	-20	40 km	
TEG-MGBS80	1550 nm	-3	3	-26	-3	-23	80 km	
TEG-MGBS10D3	TX: 1310 nm	-9	-3	-23	-3	-14	10 km	
	RX: 1550 nm							
TEG-MGBS10D5	TX: 1550 nm	-9	-3	-23	-3		-22	10 km
	RX: 1310 nm							
TEG-MGBS40D3	TX: 1310 nm	-3	3	-25	-3	-22		40 km
	RX: 1550 nm							
TEG-MGBS40D5	TX: 1550 nm	-3	3	-25	-3		-22	40 km
	RX: 1310 nm							

TRENDnet offers a limited lifetime warranty on selected fiber networking products that have been purchased in the United States/Canada on or after 1/1/2019.

SFP Dual Wavelength Single-Mode LC Module

TEG-MGBS10D3 (v4.0R)



PACKAGE CONTENTS

TEG-MGBS10D3

Quick Installation Guide

RELATED PRODUCTS

TEG-MGBS10D5	SFP Dual Wavelength Single-Mode LC Module
TL2-G244	24-Port Gigabit Layer 2 Switch w/ 4 Shared Mini-GBIC Slots
TL2-E284	24-Port 10/100 Mbps Layer 2 Switch w/ 4 Gigabit Ports and 2 Shared Mini-GBIC Slots

CONTACT INFORMATION

TRENDnet®

20675 Manhattan Place, Torrance, CA 90501 USA

Tel: 1-310-961-5500

Fax: 1-310-961-5511

Web: www.trendnet.com

Email: sales@trendnet.com

1-888-326-6061

